

# Hisense HM518

## 10" Rugged Tablet POS System

Rugged & Lightweight POS System Where Mobility Matters!



The Hisense HM518 Rugged Tablet POS is an ideal space saving solution, ideal for Retail & Hospitality applications. Operational direct from the secure docking station or instantly mobile for order taking, product creation, stock maintenance or queue busting.



**Hisense**  
Compatible  
with a Range  
of POS  
Solutions



1 0 I N C H R U G G E D T A B L E T P O S S Y S T E M



# Hisense HM518

## 10" Rugged Tablet POS System

Designed specifically for POS applications the HM518 has a host of features that regular consumer tablets don't. They include:

- Docking station with locking mechanism for stability and security.
- Physical ports on the tablet plus many more on the dock itself including Ethernet, USB, serial, VGA and cash drawer.
- Built-in hand strap mag card reader and smart card reader.
- It also has an IP54 rating and is designed to handle a 1.2m drop onto concrete.

This version of the Hisense HM518 includes a 10" flat P-CAP multi-touch display, Windows 10, 32GB of flash storage on board 2GB of ram, 1D Barcode scanner and 3G GPS slot as well as the 10" flat P-CAP multi-touch display.



### Key Features

- 10.1" Wide Screen.
- Bezel-Free, PCAP Multi-Touch Screen.
- Standard Integrated Card Reader.
- Docking Station Includes I/O Expansion Ports.
- Sturdy Hand Strap Standard.

### Other Features

- Rear Camera.
- Integrated Card Reader.
- 1 Watt Speaker.
- Sturdy Hand Strap.
- 3 LED Indicators.
- Protected Against Dust and Water Sprayed From All Directions (IP Grade IP54).
- Withstands a Drop of 4 Feet on to Concrete (MIL-STD-810G).
- HM518 Rugged Tablet Includes a Built-in Battery and MCR.
- Docking Station Includes Power Adaptor and Cord.
- Compatible with Popular Standard Applications.
- Integrated 1D Barcode Scanner.
- 3G (WCDMA GPRS).

### Optional Devices/Upgrades

- The HM518 Tablet is available with these optional upgrades:
- Integrated 2D/1D Barcode Scanner.
  - GPS – Special Order.

### Hisense

- Stylish, Space-Saving Rugged Tablet & Docking Station.



### SPECIFICATION HISENSE HM518 10" TABLET POS SYSTEM

<b>Processor:</b>		Intel Celeron Processor N2807 1.58GHz
<b>Operating System:</b>		Windows 8.1 / 10 Home / 10 Enterprise
<b>Display:</b>		10.1" TFT LCD (LED Back-Light)
<b>Resolution:</b>		1280 x 800
<b>Brightness:</b>		330 cd/m2
<b>Touch Panel:</b>		True-Flat Projected Capacitive Touch
<b>Memory:</b>		2GB RAM
<b>Storage:</b>		32GB eMMC
<b>Camera:</b>		5 Megapixel Camera (Supports 2D Barcode Function)
<b>Wireless –</b>	<b>Wi-Fi:</b>	WiFi802.11a/b/g/n/ac 2.4GHz / 5GHz
	<b>Bluetooth:</b>	Integrated Bluetooth V4.1
<b>Speaker:</b>		8 Ohm, 1 Watt Speaker
<b>Audio:</b>		3.5mm Socket
<b>MCR:</b>		Standard Integrated Triple Track Card Reader
<b>Battery –</b>	<b>Type:</b>	4000mAh (7.4V)
	<b>Life:</b>	6 Hours
<b>I/O Interface:</b>		Micro-SD Slot / SIM Card Slot / USB / Micro-USB
<b>Tablet Connector:</b>		24 Pin Pogo Style Connector
<b>Docking Station I/O –</b>	<b>USB:</b>	Three USB2.0 (2 Rear Panel / 1 Right Side)
	<b>LAN:</b>	One RJ45 (100Mbps LAN)
	<b>Serial:</b>	Two RS232C
	<b>VGA:</b>	One VGA Reserved for Second Display
	<b>Cash Drawer:</b>	One RJ11 – 12V/24V (24V Default)
	<b>DC Input:</b>	One DC Jack (12V)
<b>Power Supply:</b>		12V/3.33A External Power Adaptor 100-240V 50/60Hz
<b>Temperature –</b>	<b>Operating:</b>	32° F to 104° F (0° C to 40° C)
	<b>Storage:</b>	-4° F to 140° F (-20° C to 60° C)
<b>Humidity –</b>	<b>Operating:</b>	20% to 80% RH (Non-Condensing)
	<b>Storage:</b>	10% to 90% RH (Non-Condensing)
<b>Dimensions –</b>	<b>Tablet:</b>	10-7/8" W x 7-5/8" H x 7/8" D
<b>Safety and EMI:</b>		FCC Class-B / CE Class-B / RoHS



Bluetooth

YOUR LOCAL DEALER IS

**Hisense**

Distributed in the UK & NI by YCR Distribution Ltd. 01924 438238. Whilst every effort has been made to provide current photographs, descriptions and specifications the manufacturers reserve the right to change specifications, illustrations, model number and appearance of any item without prior notifications and therefore will not be held responsible for any variations.